


DATASHEET



RDL9CCT

230V IP44 9W LED Dimmable Downlight - CCT

www.mlaccessories.co.uk



MLA PART CODE	RDL9CCT
DESCRIPTION	230V IP44 9W LED Dimmable Downlight - CCT
NET WEIGHT (KG)	0.15
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 110 Projection - 1 Recessed Depth - 63 Minimum Void - 113
CUT-OUT (MM)	Cut-out Diameter - 92
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP44 (IP20 from above)
WATTAGE (W)	9
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	890/1020/970
LUMENS LIGHT SOURCE ONLY (LM)	1125
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	132.7
CIRCUIT WATTAGE (W)	8.5
CCT	3000/4200/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.038
DISPLACEMENT FACTOR	>0.9
SVM	0.006
PST-LM	0.16
BEAM ANGLE (DEGREES)	85

LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	Yes*
IC RATED	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
CABLE TYPE	H03VVH2-F 2 x 0.75mm ²
DRIVER	MAX. OUTPUT - 10W EFFICIENCY FULL LOAD - 82
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832986201

Date Created: 08/01/2024 15:30

