

**KISC M3X20.5/10 EK4****Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

|            |                                      |
|------------|--------------------------------------|
| Version    | Clamping yoke, Mounting screw, Steel |
| Order No.  | <a href="#">0303000000</a>           |
| Type       | KISC M3X20.5/10 EK4                  |
| GTIN (EAN) | 4008190163686                        |
| Qty.       | 100 pc(s).                           |

## KISC M3X20.5/10 EK4

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

[info@weidmueller.com](mailto:info@weidmueller.com)

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

|          |       |                 |            |
|----------|-------|-----------------|------------|
| Height   | 20 mm | Height (inches) | 0.787 inch |
| Diameter | 3 mm  | Net weight      | 1.16 g     |

### Material data

|          |        |                |               |
|----------|--------|----------------|---------------|
| Material | Steel  | Surface finish | Miscellaneous |
| Colour   | silver |                |               |

### System specifications

|         |             |
|---------|-------------|
| Version | for busbars |
|---------|-------------|

### Additional technical data

|                          |                 |                     |                 |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No              | Installation advice | Direct mounting |
| Type of fixing           | when screwed in | Type of mounting    | when screwed in |

### Dimensions

|          |      |                                     |        |
|----------|------|-------------------------------------|--------|
| Diameter | 3 mm | Metric size of the thread, external | 0 M3.0 |
|----------|------|-------------------------------------|--------|

### General

|                     |                 |                |               |
|---------------------|-----------------|----------------|---------------|
| Installation advice | Direct mounting | Surface finish | Miscellaneous |
|---------------------|-----------------|----------------|---------------|

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002848    | ETIM 7.0    | EC002848    |
| ETIM 8.0    | EC002848    | ECLASS 9.0  | 27-14-11-92 |
| ECLASS 9.1  | 27-14-11-92 | ECLASS 10.0 | 27-14-11-92 |
| ECLASS 11.0 | 27-14-11-92 | ECLASS 12.0 | 27-14-11-92 |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |   |
|--------------------|---|
| Engineering Data   | <a href="#">CAD data – STEP</a>                 |
| Engineering Data   | <a href="#">WSCAD</a>                           |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>        |