Product data sheet Characteristics

LVS08204

Floor standing enclosure, PrismaSeT G, W 600mm, H 1880mm (33M), IP30





Main

Range	PrismaSeT	
Range of product	PrismaSeT G	
Product or component type	Enclosure	
Device application	Low voltage electrical distribution	
Enclosure type	Functional enclosure delivered in kit form Metal enclosure Indoor enclosure	
Enclosure/cubicle description	Floor-standing enclosure - width 600 mm	
Kit composition	Uprights Rear plate 2 side panel Top plate Bottom plate plinth	
Additional information	Can be combined side by side	
Type of front cover	Without to be ordered separately	
Number of vertical modules [50 mm]	33	
Number of 18 mm modules per row	24	
Standards	IEC 61439-1 IEC 61439-2 IEC 62208	
Product certifications	ASTA EAC	

Complementary

[Ui] rated insulation voltage	1000 V on main rear busbars conforming to IEC 61439-2	
Network frequency	50/60 Hz	
[In] rated current	630 A at 40 °C conforming to IEC 61439-2	
Short-circuit current	50 KA	
[lcw] rated short-time withstand current	25 KA 1 s conforming to IEC 61439-1	
[lpk] rated peak withstand current	53 KA conforming to IEC 61439-1	
Electrical insulation class	Class I	
Material	Treated sheet steel	
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder	
Surface finish	Textured Matt	
Colour	White (RAL 9003)	
Width	595 Mm	
Height	1880 Mm with plinth:	

10-Aug-2022



Depth	205 Mm
Net weight	27.3 Kg
Environment	
IP degree of protection	IP30 with front plate IP40 with door IP41 with door and canopy IP43 with door, canopy and IP43 gasket
IK degree of protection	IK07 with front plate IK08 with transparent door IK10 with plain door
Mechanical robustness	Seismic tests - 2.5G conforming to IEC 60068-2-57
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	28.85 Kg
Package 1 Height	10.5 Cm
Package 1 width	66.0 Cm
Package 1 Length	190.0 Cm
Unit Type of Package 2	P2M
Number of Units in Package 2	8
Package 2 Weight	258.0 Kg
Package 2 Height	97.0 Cm
Package 2 width	120.0 Cm
Package 2 Length	202.0 Cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Droduct	Life Status :	Commercialised
Promici	i iia Siailie :	Commercialiseo

Contractual warranty

Warranty



18 months