## Product data sheet Characteristics

# LVS04014 LINERGY FM 4P DIS.BLOCK 200A 24M 54HOLES



EAN Code: 3606481870834



#### Main

Danna	I to a sum.	
Range	Linergy	
Range of product	Linergy	
Product or component type	Device feeder	
Product name	Linergy FM	
Range compatibility	PrismaSeT G enclosure PrismaSeT P enclosure Prisma PH enclosure	
Product compatibility	Spacial enclosures	
IP degree of protection	IPxx B	
ir degree of protection	IFXX D	

#### Complementary

Mounting support	DIN rail
	Plain backplate
	Slotted backplate
Installed device	Modular device
Poles description	3P + N
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 KV
[le] rated operational current	200 A
[In] rated current	200 A at 40 °C
[lpk] rated peak withstand current	20 KA
I²t on activation	6700000 A².S
Connections - terminals	Supply: crimped lug50 mm² Supply: flexible bars, 20 x 3 mm
	Distribution: quick-connect terminal strips (phase), 12 x 410 mm² (flexible)
	Distribution: quick-connect terminal strips (phase), 12 x 410 mm² (rigid)
	Distribution: quick-connect terminal strips (neutral), 18 x 410 mm² (flexible)
	Distribution: quick-connect terminal strips (neutral), 18 x 410 mm² (rigid)
9 mm pitches	48
Total number of 18 mm modules	24
Net weight	1.6 Kg
Colour	Anthracite grey (RAL 7016)

#### **Environment**

Standards	IEC 61439-1, inside enclosure IEC 61439-2, inside enclosure IEC 60947-7-1
Product certifications	ASTA

#### **Packing Units**

Facking Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.563 Kg
Package 1 Height	7.0 Cm
Package 1 width	7.8 Cm
Package 1 Length	44.5 Cm
Unit Type of Package 2	P06
Number of Units in Package 2	120
Package 2 Weight	194.0 Kg
Package 2 Height	95.0 Cm
Package 2 width	60.0 Cm
Package 2 Length	80.0 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	5
Package 3 Weight	7.838 Kg
Package 3 Height	7.0 Cm
Package 3 width	38.5 Cm
Package 3 Length	44.5 Cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant <sup>☑</sup> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	18 months

Product Life Status : Commercialised

