Product data sheet Characteristics

LVS03001 W600 MODULAR DEVICE RAIL PRISMA G





Main

IVIAIII		
Range	PrismaSeT	
Range of product	PrismaSeT G	
Product or component type	Rail	
Accessory / separate part category	Installation accessory	
Range compatibility	PrismaSeT G Prisma Pack 250	
Type of rail	Modular	
Installed device	Act 9: fixed C120 without earth leakage protection - control: toggle TeSys: fixed GV2LE TeSys: fixed GV2ME TeSys: fixed GV2RTn Acti 9: fixed iC120 without earth leakage protection - control: toggle Vigilohm: IM20 Vigilohm: IM20H Vigilohm: fixed IM9 Vigilohm: fixed IM9 Vigilohm: fixed IM9-OL ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device Multi 9: fixed modular device Multi 9: fixed NG125 without earth leakage protection - control: toggle Vigirex: RH10 Vigirex: RH21 Vigirex: RH99 Acti 9: fixed C120 with earth leakage protection - control: toggle Multi 9: fixed NG125 with earth leakage protection - control: toggle Acti 9: fixed 1/2 or 1 module lamp - horizontal installation ComPact: fixed INS125 - control: direct front rotary handle - vertical installation Acti 9: fixed measurement device - horizontal installation Multi 9: fixed modular device <= 40 A Multi 9: fixed modular device <= 40 A	
Poles description 1 x 3P: fixed C120 1 x 4P: fixed C92LE 9 x 3P: fixed GV2ME 9 x 3P: fixed GV2RT 1 x 3P: fixed GV2RT 1 x 3P: fixed iC120 1 x 4P: fixed iC120 1 x 4P: fixed iNS100 vertical installation 1 x 4P: fixed INS100 vertical installation 1 x 3P: fixed INS160 vertical installation 1 x 4P: fixed INS160 vertical installation 1 x 4P: fixed INS40 vertical installation 1 x 3P: fixed INS40 vertical installation 1 x 3P: fixed INS40 vertical installation 1 x 4P: fixed INS60 vertical installation 1 x 4P: fixed INS60 vertical installation 1 x 4P: fixed INS63 vertical installation 1 x 4P: fixed NG125 1 x 3P: fixed NG125 1 x 3P: fixed NG125 NA 1 x 4P: fixed NG125 Vertical installation 1 x 4P: fixed NG125 Vertical installation 1 x 4P: fixed NG125 NA 1 x 4P: fixed INS125 vertical installation 1 x 4P: fixed INS125 vertical installation		



Complementary	
Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Pack enclosure - width 600 mm
Number of vertical modules [50 mm]	2 module(s): 1/2 or 1 module lamp, direct in 600 mm Widefloor-standing enclosure
	2 module(s): 1/2 or 1 module lamp, direct in 600 mm Widewall-mounted enclosure
	5 module(s): C120 without earth leakage protection , direct in 600 mm Wide- floor-standing enclosure
	5 module(s): C120 without earth leakage protection , direct in 600 mm Widewal- l-mounted enclosure
	3 module(s): GV2LE, direct in 600 mm Widefloor-standing enclosure 3 module(s): GV2LE, direct in 600 mm Widewall-mounted enclosure
	3 module(s): GV2ME, direct in 600 mm Widefloor-standing enclosure
	3 module(s): GV2ME, direct in 600 mm Widewall-mounted enclosure
	3 module(s): GV2RTn, direct in 600 mm Widefloor-standing enclosure 3 module(s): GV2RTn, direct in 600 mm Widewall-mounted enclosure
	5 module(s): iC120 without earth leakage protection, direct in 600 mm Wide-
	floor-standing enclosure 5 module(s): iC120 without earth leakage protection, direct in 600 mm Widewal-
	I-mounted enclosure
	3 module(s): IM20 in 600 mm Widefloor-standing enclosure 3 module(s): IM20 in 600 mm Widewall-mounted enclosure
	3 module(s): IM20H in 600 mm Widefloor-standing enclosure
	3 module(s): IM20H in 600 mm Widewall-mounted enclosure
	3 module(s): IM9 in 600 mm Widefloor-standing enclosure 3 module(s): IM9 in 600 mm Widewall-mounted enclosure
	3 module(s): IM9-OL in 600 mm Widefloor-standing enclosure
	3 module(s): IM9-OL in 600 mm Widewall-mounted enclosure 4 module(s): INS100, direct in 600 mm Widefloor-standing enclosure
	4 module(s): INS100, direct in 600 mm Widewall-mounted enclosure
	5 module(s): INS100, direct in 600 mm Widefloor-standing enclosure 5 module(s): INS100, direct in 600 mm Widewall-mounted enclosure
	4 module(s): INS125, direct in 600 mm Widefloor-standing enclosure
	4 module(s): INS125, direct in 600 mm Widewall-mounted enclosure
	5 module(s): INS125, direct in 600 mm Widefloor-standing enclosure 5 module(s): INS125, direct in 600 mm Widewall-mounted enclosure
	4 module(s): INS160, direct in 600 mm Widefloor-standing enclosure
	4 module(s): INS160, direct in 600 mm Widewall-mounted enclosure 5 module(s): INS160, direct in 600 mm Widefloor-standing enclosure
	5 module(s): INS160, direct in 600 mm Widewall-mounted enclosure
	4 module(s): INS40, direct in 600 mm Widefloor-standing enclosure 4 module(s): INS40, direct in 600 mm Widewall-mounted enclosure
	4 module(s): INS63, direct in 600 mm Widefloor-standing enclosure
	4 module(s): INS63, direct in 600 mm Widewall-mounted enclosure 2 module(s): measurement device, direct in 600 mm Widefloor-standing enclo-
	sure
	2 module(s): measurement device, direct in 600 mm Widewall-mounted enclo- sure
	2 module(s): measurement device, direct in 600 mm WidePack enclosure 3 module(s): modular device <= 40 A, direct in 600 mm Widefloor-standing enclosure
	3 module(s): modular device <= 40 A, direct in 600 mm Widewall-mounted enclosure
	8 module(s): modular device <= 40 A, direct in 600 mm Widefloor-standing enclosure
	8 module(s): modular device <= 40 A, direct in 600 mm Widewall-mounted enclo- sure
	6 module(s): modular device <= 40 A, direct in 600 mm WidePack enclosure 6 module(s): modular device, direct in 600 mm WidePack enclosure
	4 module(s): modular device, direct in 600 mm Widefloor-standing enclosure
	4 module(s): modular device, direct in 600 mm Widewall-mounted enclosure 5 module(s): NG125 without earth leakage protection, direct in 600 mm Widefloor-standing enclosure
	5 module(s): NG125 without earth leakage protection , direct in 600 mm Widewal- l-mounted enclosure
	5 module(s): NG125 NA, direct in 600 mm Widefloor-standing enclosure 5 module(s): NG125 NA, direct in 600 mm Widewall-mounted enclosure
	3 module(s): RH10, direct in 600 mm Widefloor-standing enclosure
	3 module(s): RH10, direct in 600 mm Widewall-mounted enclosure 3 module(s): RH21, direct in 600 mm Widefloor-standing enclosure
	3 module(s): RH21, direct in 600 mm Widewall-mounted enclosure
	3 module(s): RH99, direct in 600 mm Widefloor-standing enclosure 3 module(s): RH99, direct in 600 mm Widewall-mounted enclosure
	5 module(s): C120 with earth leakage protection, direct in 600 mm Widefloor-s-
	tanding enclosure 5 module(s): C120 with earth leakage protection , direct in 600 mm Widewal-

Width	468 Mm	
Depth	100 Mm	
Net weight	0.24 Kg	
Colour	Natural	
Material	Metal	

Environment

Standards	IEC 61439-2 IEC 61439-1	
Product certifications	ASTA	

Packing Units

Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	253.0 G
Package 1 Height	5.4 Cm
Package 1 width	9.6 Cm
Package 1 Length	47.0 Cm
Unit Type of Package 2	CAR
Number of Units in Package 2	25
Package 2 Weight	6.87 Kg
Package 2 Height	14.0 Cm
Package 2 width	48.0 Cm
Package 2 Length	50.0 Cm
Unit Type of Package 3	P12
Number of Units in Package 3	300
Package 3 Weight	94.0 Kg
Package 3 Height	62.0 Cm
Package 3 width	80.0 Cm
Package 3 Length	120.0 Cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status:	Commercialised	
----------------------	----------------	--

