Product data sheet
Characteristics

LVS03803
PLAIN FRONT PLATE W600/W650 3M

Green Premium™ Product

Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT G enclosure PrismaSeT P cubicle PrismaSeT Pack 160 enclosure
Type of front plate	Plain
Installed device	TeSys: fixed D or K contactors <= 40 A - horizontal installation
Poles description	9 x 4P: modular rail support: D or K contactors <= 40 A horizontal installation

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm Pack enclosure - width 555 mm
Connection position	Direct connection
Number of vertical modules [50 mm]	3
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA
Material	Steel
Surface finish	Textured Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	150 Mm
Width	500 Mm
Net weight	0.68 Kg
Quantity per set	Set of 1
Enclosure/cubicle width	600 mm PrismaSeT G floor-standing enclosure TeSys D or K contactors <= 40 A fixed horizontal 4P 9 direct 3 600 mm PrismaSeT G wall-mounted enclosure TeSys D or K contactors <= 40 A fixed horizontal 4P 9 direct 3 650 mm 400 mm PrismaSeT P cubicle TeSys D or K contactors <= 40 A fixed-horizontal 4P 9 direct 3 555 mm Pack 160 Pack enclosure TeSys D or K contactors <= 40 A fixed horizontal 4P 9 direct 3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	676.0 G
Package 1 Height	3.0 Cm
Package 1 width	16.4 Cm
Package 1 Length	51.0 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	6.935 Kg
Package 2 Height	16.5 Cm
Package 2 width	17.5 Cm
Package 2 Length	52.5 Cm
Unit Type of Package 3	P12
Number of Units in Package 3	450
Package 3 Weight	323.5 Kg
Package 3 Height	96.0 Cm
Package 3 width	80.0 Cm
Package 3 Length	120.0 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months

Product Life Status :	Commercialised

Schneider Electric