



## 507346LW

SWITCHED SOCKET WITH MECHANICAL INTERLOCK



| Registry              |               | Technical data            |                     |
|-----------------------|---------------|---------------------------|---------------------|
| Net weight            | 2,6           | Frequency                 | 50-60Hz             |
| EAN Code              | 8014950035021 | Protection level          | IP65                |
| Old Material Number   | PM63/3408FPB  | Poles                     | 3P+N+ $\frac{1}{2}$ |
| Reference Standards   | Directive     | Clock Position            | 6                   |
| EN 60309-1/A1: 2007   | 2014/35/EU    | Nominal Operating Voltage | 400V                |
| EN 60309-1/A1EC: 2014 |               | Nominal current           | 63A                 |
| EN 60309-1/A2: 2012   |               | Execution                 | WALL MOUNTING       |
| EN 60309-1: 1999      |               | Insulation Class          | II                  |
| EN 60309-2/A1: 2007   |               |                           |                     |
| EN 60309-2/A2: 2012   |               |                           |                     |
| EN 60309-2: 1999      |               |                           |                     |
| EN 60309-4/A1: 2012   |               |                           |                     |
| EN 60309-4: 2007      |               |                           |                     |
| Marks                 |               |                           |                     |
|                       |               |                           |                     |