

**TRB/TRR/TRY - RING TERMINALS**

Description:

Finish: Tin Plated

Voltage: 600V @ 75°C

Insulated: Polyvinyl Chloride

Conform to BS4579 & BS4G178



**OTHER ADDITIONAL INFORMATION**

Code	Colour	Ring Diameter (mm)	Conductor Size	Amp Rating
TRR32	Red	3.2mm (6BA)	0.25mm <sup>2</sup> - 1.5mm <sup>2</sup>	19
TRR37	Red	3.7mm (4BA)	0.25mm <sup>2</sup> - 1.5mm <sup>2</sup>	19
TRR43	Red	4.3mm (3BA)	0.25mm <sup>2</sup> - 1.5mm <sup>2</sup>	19
TRR53	Red	5.3mm (2BA)	0.25mm <sup>2</sup> - 1.5mm <sup>2</sup>	19
TRR64	Red	6.4mm (0BA)	0.25mm <sup>2</sup> - 1.5mm <sup>2</sup>	19
TRR85	Red	8.4mm (5/16)	0.25mm <sup>2</sup> - 1.5mm <sup>2</sup>	19
TRR10	Red	10.5mm (3/8)	0.25mm <sup>2</sup> - 1.5mm <sup>2</sup>	19
TRB32	Blue	3.2mm (6BA)	1.1mm <sup>2</sup> - 2.5mm <sup>2</sup>	27
TRB37	Blue	3.7mm (4BA)	1.1mm <sup>2</sup> - 2.5mm <sup>2</sup>	27
TRB43	Blue	4.3mm (3BA)	1.1mm <sup>2</sup> - 2.5mm <sup>2</sup>	27
TRB53	Blue	5.3mm (2BA)	1.1mm <sup>2</sup> - 2.5mm <sup>2</sup>	27
TRB64	Blue	6.4mm (0BA)	1.1mm <sup>2</sup> - 2.5mm <sup>2</sup>	27
TRB8	Blue	8.4mm (5/16)	1.1mm <sup>2</sup> - 2.5mm <sup>2</sup>	27
TRB10	Blue	10.5mm (3/8)	1.1mm <sup>2</sup> - 2.5mm <sup>2</sup>	27
TRY43	Yellow	4.3mm (3BA)	2.7mm <sup>2</sup> - 6.0mm <sup>2</sup>	48
TRY53	Yellow	5.3mm (2BA)	2.7mm <sup>2</sup> - 6.0mm <sup>2</sup>	48
TRY64	Yellow	6.4mm (0BA)	2.7mm <sup>2</sup> - 6.0mm <sup>2</sup>	48
TRY8	Yellow	8.4mm (5/16)	2.7mm <sup>2</sup> - 6.0mm <sup>2</sup>	48
TRY10	Yellow	10.5mm (3/8)	2.7mm <sup>2</sup> - 6.0mm <sup>2</sup>	48
TRY12	Yellow	13.0mm (1/2)	2.7mm <sup>2</sup> - 6.0mm <sup>2</sup>	48

