Xnightsbridge

DATASHEET



SF8900MB

115V/230V Dual Voltage Shaver Socket - Matt Black with Black Insert

www.mlaccessories.co.uk

DESCRIPTIONNET WEIGHT (KG)0.4FINISHMatt BlackINSERT COLOURBlackDIMENSIONS (MM)Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4MINIMUM MOUNTING BOX DEPTH47mmCONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP41INPUT VOLTAGE230V 50HzSECONDARY VOLTAGE115/230VEARTH TERMINALYes
FINISH INSERT COLOUR Black Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CLASS I IP RATING INPUT VOLTAGE SECONDARY VOLTAGE Matt Black Matt Black CHASS Height - 147.5 Vidth - 87.5 Projection - 4.3 Recessed Depth - 43.4 ATMM CONSTRUCTION Construction - Premium grade steel IP41 INPUT VOLTAGE 230V 50Hz SECONDARY VOLTAGE
INSERT COLOUR Black Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING INPUT VOLTAGE SECONDARY VOLTAGE Black Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 CONSTRUCTION CONSTRUCTION IP41 INPUT VOLTAGE SECONDARY VOLTAGE
DIMENSIONS (MM) Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING IP41 INPUT VOLTAGE SECONDARY VOLTAGE Height - 147.5 Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 CONSTRUCTION IP41 IP41 IP41 IP41 INPUT VOLTAGE SECONDARY VOLTAGE
DIMENSIONS (MM) Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION IP RATING IP41 INPUT VOLTAGE SECONDARY VOLTAGE Width - 87.5 Projection - 4.3 Recessed Depth - 43.4 Construction - Premium grade steel I IP41 IP41 INPUT VOLTAGE SECONDARY VOLTAGE
CONSTRUCTION Construction - Premium grade steel CLASS I IP RATING IP41 INPUT VOLTAGE 230V 50Hz SECONDARY VOLTAGE 115/230V
CLASS I IP RATING IP41 INPUT VOLTAGE 230V 50Hz SECONDARY VOLTAGE 115/230V
IP RATING IP41 INPUT VOLTAGE 230V 50Hz SECONDARY VOLTAGE 115/230V
INPUT VOLTAGE 230V 50Hz SECONDARY VOLTAGE 115/230V
SECONDARY VOLTAGE 115/230V
EARTH TERMINAL Yes
LOAD/MAX. LOAD 20VA
TERMINAL CAPACITY 2 x 2.5mm² or 1 x 4.0mm²
WARRANTY 25year(s)
MANUFACTURED IN ACCORDANCE WITH BS EN 61558-2-5
ORIGIN OF MANUFACTURE China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes
EAN 5055832903857

Date Created: 08/01/2024 12:01





