



General Information

Dimensions	227mm (L) x 34mm (H) x 24mm (D)
Materials	Body: Polycarbonate Diffuser: Polycarbonate
Finish	White (RAL 9016)
Product Weight	0.095Kg
Dimmable	No
Ingress Protection	IP20
Warranty	3 Years

Supply & Power

Input Voltage & Frequency	220-240V~ 50Hz
Electrical Safety	Class II (Double Insulated)
Circuit Wattage	3.5W
Input Current	35mA
Power Factor	>0.5
Ambient Temperature (Ta)	-30°C - +40°C
Input Mains Cable	2 x 0.75mm ² H03VVH2-F - 1 Metre (Supplied)
Number Fitted Together	28 Units (If Mixed Sizes Then Total Wattage Must Not Exceed 100W)

Luminaire Output

	3000K	4000K
Typical Luminous Flux	298lm	321lm
Efficacy	85lm/W	85lm/W
Beam Angle	130°	
CRI	>80	
LED Lifetime (L70)	35,000 Hours	

Accessories

OVLL89250	250mm Link Lead For Cubi Undercupboard Lights
OVLL89500	500mm Link Lead For Cubi Undercupboard Lights
OVLL891000	1000mm Link Lead For Cubi Undercupboard Lights

